

Connect the two IP segments using the core switch



AI Overview

To connect two IP network segments using a core switch, you typically use VLANs on Layer 3 switches and configure routing between them.

Step 1: Determine Switch Capabilities Layer 2 switches can only forward traffic based on MAC addresses and cannot route between different IP subnets. Communication between different network segments requires a router or a Layer 3 switch. Layer 3 (core) switches can perform routing functions, allowing inter-VLAN communication and connecting multiple IP network segments directly.

Step 2: Create VLANs for Each Network Segment Assign each IP network segment to a separate VLAN on the core switch. For example, VLAN 10 for 192.168.10.0/24 and VLAN 20 for 192.168.20.0/24. Configure access ports on edge switches to belong to the appropriate VLANs and trunk ports to carry multiple VLANs to the core switch.

Step 3: Assign IP Addresses to VLAN Interfaces On the core switch, create VLAN interfaces (SVIs) for each VLAN and assign an IP address that will act as the default gateway for devices in that VLAN. For example: VLAN 10 interface: 192.168.10.1/24 VLAN 20 interface: 192.168.20.1/24

Step 4: Configure Routing Between VLANs Enable IP routing on the core switch to allow traffic to flow between VLANs. For small or stable networks, you can configure static routes pointing to each VLAN network. For larger or dynamic networks, consider using a dynamic routing protocol like OSPF or RIP.

Step 5: Verify Connectivity Test communication by pinging devices across VLANs. Ensure that devices use the VLAN interface IP as their default gateway. Check that trunk links between switches allow all required VLANs to pass through.

Optional: Security and Management Use Access Control Lists (ACLs) to restrict traffic between VLANs if needed. Monitor routing tables and VLAN assignments to ensure proper segmentation and performance. By following these st...

Article Content

Sx300 Series Switches Typical Configuration Examples (V200)

Example for Configuring Communication Between Different Network Segments Through Static Routes Overview In addition to configuring an IP address for a VLANIF interface, you need to configure a

connect two subnets via switch

At work I was asked to connect the following two different subnet using cisco 2960x switch. all the switches we have are cisco catalyst 2960x

How To Configure A Switch For Network Segmentation?

By following this comprehensive guide, you can effectively learn how to configure a switch for network segmentation, enhancing your network's security, performance, and manageability.

Bridges (local Internetworking device)

Prerequisites - Network Devices, Types of switches Bridge is a local internetworking device that is used to connect two or more network segments together. A bridge operates at the Data

two different networks through one switch

I need this: two connections coming off of the firewall (each connection hosting a different subnet), going into the Cisco switch. Then one connection (coming off of the Cisco) hosting the traffic

What is a Network Bridge in Computer Networks?

A network bridge is a device that connects two or more network segments to allow the devices on different segments to communicate. Network

Intercommunication between routers on different

When a router is connected to another router, and the two routers are connected to different network segments, in order for the two network segments

Best practice for chaining switches together?

Two 10gb fibres connect adjacent pairs of buildings so as to form a "ring". The switches will present numerous vlans on their access ports. Some vlans are unique to a given building and will

Can Switches Interconnect Different Network Segments? (With

Layer 2 switches work at the data link layer and forward data frames based on MAC addresses, and they must use routers to realize the interconnection between different network

L2 communication between different network segments

Is it possible to communicate between two different network segments within a single vlan? Both devices on VLAN1, untagged. 10.9.10.10/24 communicating with 192.168.1.33/24 via layer

What is optimal way to connect two core switch/routers

We have two 4507s at our core, running HSRP. We have three other 4507s at the edge, plus eight 2950s. All edge switches and WAN routers are connected to both core 4507s. We have a Port-Group

networking

I would like to join/bridge two different networks, network 1 and network 2: Network 1: A network consisted of a Linux box (with one ethernet)

L3 or L2 Link between Core Switches

A more proper design would be to put them into a data center, as the data center has its own access and distribution (sometimes called aggregation) layer switches, and the distribution

2 separate networks connected to one switch?

In my organization, we have 2 networks. A network for staff and another network for public Wi-Fi. I will have to use a switch, because there is a computer that has to be connected to the

Network Segmentation: Everything You Need to Know

Two common examples are VLANs and Layer 3 IP addressing schemes: VLANs (virtual local area networks) configure switch ports into isolated

networking

If I connect from outside to the VPN of the LTE-Router I want to access all devices in the 192.168.0.1/24 subnet (for e.g. device 2). Connected to

Routing Between VLANs & Layer 3 Switches

Learn what a Router Sub-interface and a L3 Switch is, as well as how to configure both of them on Cisco devices to enable Routing between VLANs.

Splitting a single ISP line through a core switch to 2 ...

What my supervisor did was created a VLAN on three unused ports on our core switch stack, plugged in the main ISP line into that VLAN, and attached the two firewalls to the other two ports of that VLAN.

LAN segmentation with different IP addresses

Since you would need a layer-3 device of some sort (i.e. the router you mentioned) to communicate between the two networks you want to create, VLANs may help with segmentation of

Using one Layer 3 switch for different segments

2- want to create Vlan on few ports that would be exposed to public 3- want to create vlan for internal use machines with dual Ethernet one exposed

Configure Inter VLAN Routing with Multiple Switches

Access Switches On the Access switches that end user devices are going to connect to, all we really have to do is create the additional VLANs. On

Can switches interconnect different network segments? (with ...

To sum up, Layer 2 switches need to be paired with routers to realize the purpose of interconnection between different network segments, while Layer 3 switches do not need to build

Configuring the Core Switch

In this scenario, IP addresses of the interfaces connecting the core switch to the BRASs and firewalls and OSPF need to be configured on the core switch, so as to implement connectivity

Level 2 Routing: LAN Bridges and Switches

The easier way to do this is via a bridge. We will describe how simple bridges work first, and then discuss an advanced form of bridges called switches, which today are in common use. The

Network with inter vlan routing

I have two routers (in my opinion for redundancy like HSRP). They are connected to 2 core switches L3 (in my opinion also for redundancy like

connect two subnets via switch

Hi there, I am a electronics engineer, not a network engineer. but I have done some basic cisco course, so I can understand some of the

Connecting Core to Access switches

I would recommend at least 2 copper runs per switch, which you can then put in a port channel, so that you have 2 Gbps of uplink for all of your edge switches. If you are planning on just

How to connect two IP network segments using a core switch

Sailing Poland Optoelectronic Systems (SPO) supplies fiber optic infrastructure: optical transceivers, PLC splitters, ODF racks, patch cords, FTTH cabling, optical switches, and 5G fronthaul solutions for

Sx300 Series Switches Typical Configuration Examples (V200)

In addition to configuring an IP address for a VLANIF interface, you need to configure a static route or a dynamic routing protocol when PCs on different network segments across several switches need to

Merging two networks

A switch is a bridge. To connect the two networks together at layer 2, all you have to do is to connect a cable between the 2 existing switches. However: if both networks use different IP addressing, they

How to configure two Core switches in a network with intervlan routing ...

Dear All, Hi Friends, i have two 3750 switches. I configured intervlan routing between three vlans which are vlan11,vlan12, and vlan13 in Core Switch1. These three vlans are communicate each

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.sabineamsee.co.za>

Email: info@sabineamsee.co.za

Phone: +27 82 415 6793

Address: Unit 7, Innovation Park, 34 Electron Road, Kempton Park, 1620, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

